

SUPERDECK®

Semi-Transparent Waterborne Stain

2400 Series



General Description

- Enhanced formula delivers premium performance for up to three years*
- Advanced UV Protection
- Excellent penetration for protecting horizontal exterior wood surfaces
- Can be applied to damp surfaces (not to exceed 25% moisture content) allowing surfaces to be prepared and stained in one day
- Contains agents which inhibit the growth of mildew on the surface of the coating

Recommended Substrates

- For use on decks, steps, rails spindles, patios, walkways, outdoor wood furniture.
- Use on Pressure Treated, Cedar, Redwood, Pine Cypress, Fir and Spruce

Tinting & Base Color Information

Tint Base - Must be tinted before use

Features

3 Year Limited Warranty against cracking and peeling
Advanced UV protection

Product Application

SURFACE PREPARATION:

All surfaces must be clean, dry, and free from dirt, mildew stains, dust and other foreign matter. Do not apply over sealed surfaces. For wood surfaces remove surface stains, dirt and failed oxidized stains with Superdeck® Wood Cleaner. Remove all loose peeling paint, rinse thoroughly with water and allow to completely dry before coating. **WARNING!** Removal of old paint by sanding, scraping, or other means may generate dust or fumes that may contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

PRODUCT PREPARATION:

Thoroughly stir contents before and occasionally during use. For uniformity, mix all cans together before use. Do not thin or mix with any other stains or coatings. All surfaces must be clean, dry, and free from dirt, mildew stains, dust and other foreign matter. Be sure to follow directions for maximum product performance.

THINNING:

Do not thin.



Product Application (cont.)

APPLICATION:

Carefully follow all label instructions. Thoroughly rinse the surface to remove all residue and allow to thoroughly dry before coating. Test the absorbency of the wood by sprinkling water on the surface. If the water penetrates into the wood quickly, the wood is ready to finish. If the water beads up or does not penetrate, allow the wood to weather 1 to 2 weeks and test for absorbency again. Penetration will vary depending on porosity and water content of the surface. Thoroughly coat cut ends and joints. For best results apply in shade with surface temperatures between 50°F and 90°F. Cooler temperatures require longer drying times. After application, while the material is still wet, back brush to force the material into the wood fibers and to achieve a uniform appearance. Two coats are required for proper color development, the second coat **MUST** be applied within 7 days of the first coat.

APPLICATION TEMPERATURE:

For best results apply in shade with surface temperatures between 50°F and 90°F. Do not apply if rain or snow is expected within 24 hrs after application. Air and surface temperatures must not drop below 50°F for the first 24 hrs after application. Cooler temperatures require longer drying times.

DRY TIME @ 77°F, 50% RH:

1 Hour to touch.

Recoat: 4 hr. minimum - 7 days maximum.

Drying and recoat times are temperature, humidity and film thickness dependent.

Two coats are required for proper color development, the second coat **MUST** be applied within 7 days of the first coat.

SPREAD RATE:

Smooth: 350 sq ft/gal

Rough/Porous: 100-200 sq ft/gal

Depending on porosity and texture

New wood normally requires less product than old, weathered wood. This is due to older wood being more porous than newer wood.

Product Application (cont.)

CLEAN UP:

Clean spills, spatters, and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.

Physical Properties

<i>VEHICLE TYPE:</i>	Acrylic
<i>WEIGHT PER GAL:</i>	8.94 lbs/gal
<i>SOLIDS % WT:</i>	28 ± 2%
<i>SOLIDS % VOLUME:</i>	23 ± 2%
<i>FLASH POINT:</i>	N/A
<i>V.O.C.:</i>	<50 g/L; 0.42 lb/gal
Coverage:	100-350 sq. ft. per gallon

Cautions

CAUTIONS: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

Conformance

OTC Approved:	Yes
SCAQMD Approved:	Yes
LADCO Approved:	Yes
CARB Approved:	Yes
CARB SCM 2007 :	Yes

Packaging

1-Gallon Container - 126 fl oz 3.73 L
5-Gallon Pail - 630 fl oz 18.63 L

3 Year Limited Warranty

If this product, when applied according to product application instructions to a properly prepared exterior surface, peels or blisters within 3 years from the date of purchase, manufacturer shall, upon presentation of proof of purchase, either replace an equivalent quantity of product sufficient to repair the peeling or blistering free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous product or improper application. This is your sole remedy under this warranty. To obtain performance under this warranty, contact manufacturer at (800) 825-5382 or superdeck.com. You may be asked to contact the retailer from whom you purchased this product for further warranty instructions. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

10/10 (16)